



## STEEL CRASH BARRIER- MEISER RAIL 4.0



Meiser Rail 4.0 is a steel guardrail system from Meiser Strassenausstattung. It is tested in accordance with EN 1317-1:2010, EN 1317-2:2010 and EN 1317-5:2007+A2:2012/AC:2012. It is used as a single-sided guardrail in outer and central reservations and offers good performance combined with very low weight. The steel grade is S355JR.

### System Description

Meiser Rail 4.0 is classified at containment level N2/H1, has a working width of W3, an ASI value of A, and a dynamic deflection of 0.9 m. The guardrail is 0.20 m wide, 0.75 m high, and has an installation length of 48 metres.

### Installation

Meiser Rail 4.0 is installed with a post spacing of 4.0 m using post type C-125 mm.

### Bolts

According to EN ISO 898-1:

M16x30, quality class 8.8

M16x45, quality class 8.8

Technical data				
Containment Level	Working Width	ASI	Post Spacing	Post Type
N1	W3	A	4,00	C-125 mm
H1	W3	A	4,00	C-125 mm

DAV NORDIC A/S  
Tietgensvej 12  
DK-8600 Silkeborg

DAV NORDIC A/S  
Pilebækvej 5  
DK-4632 Bjæverskov

DAV NORDIC A/S  
+45 86822900  
info@davnordic.dk

