



STEEL CRASH BARRIER- STALPRO RAIL HD



StalPro Rail HD is a steel guardrail system from Stalprodukt S.A. It has been tested in accordance with EN 1317-5. It is used as a single-sided guardrail in outer and central reservations. The steel grade is S355MC according to EN 10149-2.

System Description

StalPro Rail HD is classified at containment levels H1/H2, has a working width of W3/W4, an ASI value of A, and a dynamic deflection of 0.5 m. The guardrail is 0.40 m wide, 0.75 m high, and has a minimum installation length of 60 metres.

Installation

StalPro Rail HD is installed with a post spacing of 1.33 m using post type C-120 mm.

Bolts

According to EN ISO 898-1:

M16x25, quality class 8.8

M16x40, quality class 5.8

M16x40, quality class 4.6

| Technical data | | | | |
|-------------------|---------------|-----|--------------|-----------|
| Containment Level | Working Width | ASI | Post Spacing | Post Type |
| H1 | W3 | A | 1,33 | C-120 mm |
| H2 | W4 | A | 1,33 | C-120 mm |

DAV NORDIC A/S
Tietgensvej 12
DK-8600 Silkeborg

DAV NORDIC A/S
Pilebækvej 5
DK-4632 Bjæverskov

DAV NORDIC A/S
+45 86822900
info@davnordic.dk

